

PG Series | LK20P22

# CONSTRUCTION FORKLIFTS

HEAVY DUTY. UNIQUE MILITARY DESIGN.



### Specifications PG Series: LK20P22

<b>Capacity @ 24" LC</b>	20,000 lbs. (9070 kg)	<b>Drive</b>	2 Wheel, Front
<b>Length, Less Forks</b>	260" (6605 mm)	<b>Steering</b>	2 Wheel, Rear
<b>Width</b>	97" (2465 mm)	<b>Lift Height</b>	168" (4265 cm)
<b>Height - Overhead Guard</b>	129" (3275 mm)	<b>Carriage Width</b>	60" (1525 mm)
<b>Wheelbase</b>	110" (2795 mm)	<b>Tilt Forward</b>	10°
<b>Turning Radius</b>	173" (4395 mm)	<b>Tilt Backward</b>	15°
<b>Ground Clearance</b>	11" (280 mm)	<b>Fork Length</b>	48" (1220 mm)
<b>Weight</b>	31,000 lbs (14,060 kg)	<b>Electrical System</b>	12v Or 24v

<b>ENGINE</b>	Perkins Tier 3, 4 Cylinder 141 hp (105 kW) Turbo Diesel
<b>TRANSMISSION</b>	2-Speed Powershuttle
<b>AXLE - DRIVE</b>	Internal Reduction with Planetary Hubs
<b>AXLE - STEER</b>	High Steer Angle with Oscillating Mount
<b>SERVICE BRAKES - DRIVE/STEER</b>	Drum, Hydraulic / Disc, Hydraulic
<b>PARKING BRAKE</b>	Drum on Transmission Output, Manual
<b>TIRES - ALL</b>	Non-Directional Lug. 9.00 x 20
<b>CAPACITIES - FUEL/HYDRAULIC</b>	85 US Gallons (303 L)

## Liftking's LK20P22 - A Modern Day Workhorse

*Design to military specifications then adapted for commercial use, the LK20P22 is unique in many ways.*

- One of the main design criteria's was to maximize productive uptime by eliminating all non-critical components, thereby reducing potential points of failure while simplifying maintenance and repairs.
- Run time between fuel fill-ups is extended by utilizing an extra-capacity fuel tank while the equally large hydraulic tank allows greater intervals between hydraulic system servicing.
- The six engine compartment maintenance doors allow unfettered access to vital mechanical components while all routine maintenance points are strategically located for quick and easy daily checks.



## Standard Equipment

Heavy Duty Clearview Roller Mast with Dual Chains • Hydraulic Fork Positioner • FOPS Operator Compartment • Hydraulic Brakes • Power Steering • Soft-Shift Powershift Transmission • Tier 3 Turbo Diesel Engine • Headlights and Tail Lights • Wide Grip Handrails • Ion-Nitride Cylinder Rods • Extra Wide Steps • Asbestor-Free Brake Linkings • Trailer Hitch • Electric Horn and Automatic Backup Alarm • Tilt Steering Column with Anti-Start Ignition and Neutral Safety Interlock • Adjustable Seat • Extra Thick Fenders for Maximum Safety and Durability • Engine Oil Pressure Gauge, Fuel Gauge, Hour Meter, and Warning Lights • Operator, maintenance and illustrated parts manuals included • 1 Year 2000 hours limited warranty (2 year engine warranty).

## Optional Equipment

Various mast/carriage/fork types and sizes • Various engines • Lockable engine hood, fuel tank and hydraulic caps • Air Pre-Cleaner • Fluid Sampling Ports • High Durability Powder Coat Paint • Adjustable Height Strobe Light and Additional Lighting • DS Safety Rating • Tinted Windows • Sunvisor • Power Assisted Brakes • Deadman seat • Safety-Start Seatbelt • Heated Mirrors • Cold Weather Package • 12V Outlet • Radio • Cupholders • Weight Scale • Enclosed all weather operator compartment with HD heater, sliding windows, wipers, lift-off split doors • ROPS Operator Compartment • Air Conditioning • Air ride suspension seat with arm rests and retractable safety belt • Frame level • Foam filled tires • Towing package • Contact dealer for other options.



Liftking reserves the right to make changes in specifications shown, herein, and improvements, or discontinue manufacture at any time without notice or obligation. The information contained herein is general in nature and is not intended for specific application purposes.



Liftking is ISO 9001:2015 registered (EN ISO 9001:2015; BS EN ISO 9001:2015; ANSI/ASQ Q9001:2015)

7135 Islington Avenue, Woodbridge, Ontario. L4L 1V9  
Tel: 905-265-3965 | Fax: 905-851-6396